

Wires, Cables & Connectors



Top quality, affordable wires and cables make solid, dependable connections in your installations



- · All cables and connectors UL® listed
- Ideal for battery interconnects and inverter home runs
- · Wide variety of lengths and sizes available
- · Custom lengths available

| Cable Size (AWG) | Lengh | Unit | Color | Insulation Type |
|---------------------|---|------|----------------------|--------------------|
| #2 | 12, 18 | inch | Black or Red | THWN-2 |
| #6 | 12 | inch | Red | THWN-2 |
| 2/0 | 12, 18, 24, 36, 48, 60, 120 | inch | Black, Red, or White | THWN-2 |
| 4/0 | 12, 18, 24, 36, 60, 120, 180 | inch | Black, Red, or White | THWN-2 |
| MC Cables* | 2, 3, 4, 6, 8, 10, 12, 15, 20, 25, 30, 40, 50, 75, 100, 150 | foot | Black | USE-2 |

^{*}MC Cables include both the male and female connectors and a "Do Not Disconnect Under Load" label.

ReadyWatt® Wires and Cables are UL® listed and built to manufacturers specifications with manufacturer-approved assembly equipment.

ReadyWatt® battery and inverter cables are made using Cobra X flex cable and crimp connectors UL® listed for Class K fine stranded wire. This cable offers a unique flame retardant polyvinyl chloride compound (VW-1), and is moisture, abrasion, acid, diesel fuel, and oil resistant. It is extremely flexible and easy to work with. All connectors are sealed using a mastik filled heat shrink to reduce corrosion. MC cables are also sunlight resistant.

Custom sizes and configurations are also available.

Designed, built and distributed by:



800 GO SOLAR (800.467.6527) • groSolar.com

© 2008 Global Resource Options, Inc. All rights reserved. OR CCB Lic. #180494 gro, groSolar, and ReadyWatt are trademarks of Global Resource Options, Inc.

| Offered by: | | | |
|-------------|--|--|--|
| | | | |
| | | | |
| | | | |