



FRONIUS IG

GRID-TIED INVERTERS FOR PHOTOVOLTAIC SYSTEMS

Light Weight

At 26 lbs, the FRONIUS IG inverters are the lightest grid-connected inverters making them easy and cost effective to install.

Flexible

The wide voltage range of 150-500 V allows you to use different types of modules and system configuration possibilities.

Lower Cost

Integrated UL approved DC & AC disconnects which reduce installation time and complexity - often eliminating the need for additional disconnects.

LCD Display

User-friendly and comes standard with every FRONIUS IG; tracks more than 20 critical system performance parameters.

Plug-and-Play

Expansion slots in the inverter allow you to easily upgrade the inverter with data communication options.

Reliable

Fronius has been in business for over 60 years and has more than 200,000 FRONIUS IG inverters installed worldwide.

Warranty

10 year Premium Warranty.



POWERING YOUR FUTURE

FRONIUS IG

FRONIUS IG 4000 / 5100 / 4500-LV - Specifications

DC Input Data	FRONIUS IG 4000	FRONIUS IG 5100	FRONIUS IG 4500-LV
Recommended PV power	3000 – 5000 Wp	4000 – 6300 Wp	3600 – 5500 Wp
Max. DC input voltage	500 V	500 V	500 V
Operating DC voltage range	150 – 450 V	150 – 450 V	150 – 450 V
Max. usable DC input current	26.1 A	33.2 A	29.3 A
AC Output Data	FRONIUS IG 4000	FRONIUS IG 5100	FRONIUS IG 4500-LV
Maximum output power @40° C	4000 W	5100 W	4500 W
Nominal AC output voltage	240 V		
Utility AC voltage range	212 – 264 V (240 V +10% /-12%)		183 – 229 V
Maximum AC current	16.7 A	21.3 A	21.6 A
Maximum utility back feed current	0.0 A	0.0 A	0.0 A
Operating frequency range	59.3 – 60.5 Hz (60 Hz nom)		
Total harmonic distortion	< 5 %		
Power Factor (cos phi)	1		
General Data	FRONIUS IG 4000	FRONIUS IG 5100	FRONIUS IG 4500-LV
Max. efficiency	95.2 %	95.2 %	94.4 %
Consumption in stand-by	< 0.15 W (night)		
Consumption during operation	15 W		
Enclosure	NEMA 3R		
Size (l x w x h)	28.4 x 16.5 x 8.8 in (720 x 418 x 223 mm)		
Weight	42 lbs. (19 kg)		
Ambient temperature range	-5 to 122 °F (-20 to +50 °C)		
Cooling	controlled forced ventilation		
Integrated DC and AC disconnects	standard UL approved DC & AC disconnects		
Protections			
Ground fault protection	Internal GFDI, in accordance with UL 1741		
DC reverse polarity protection	Internal diode		
Islanding protection	Internal, in accordance with UL 1741, IEEE 1547		
Over temperature	Output power derating		
Surge Protection	Internal DC & AC protection, Tested to 6 kV		
Compliance			
Safety	UL 1741		
EMI	FCC Part 15; Class A & B		
Anti-Islanding protection	UL 1741, IEEE 1547		
Ground fault detector and interrupter	Compliant with NEC Art. 690 requirements, UL 1741		
Miscellaneous			
Maximum AC over current protection	Two-pole, 30 A circuit breaker		
AC wire sizing	Use maximum AWG 6 194°F (90 °C) copper wire		
DC wire sizing	Use maximum AWG 6 194°F (90 °C) copper wire		
AC disconnect	32 A		
DC disconnect	40 A		
Warranty	10 year Premium Warranty is Standard		

Sold by:



Fronius USA LLC
 Solar Electronic Division
 10421 Citation Drive
 Suite 1100 Brighton, MI 48116
 Phone: 810-220-4414
 Fax: 810-220-4424
 E-Mail: pv-us@fronius.com
 www.fronius-usa.com

Supplied by:



groSolar.com
 800.467.6527
 ORCCB Lic #180494

Text and illustrations technically correct at time of going to print. We reserve the right to make modifications. This document may not be copied or otherwise reproduced without the express prior written consent of Fronius International GmbH

40,0006,2543 (1/08)